















# Gantom Series

## Lighting Fixtures



PRODUCT NAME	<b>Gantom DMX Spot</b> RGBW/DW Spotlight	<b>Gantom DMX Flood</b> RGBW/DW Floodlight	<b>Gantom iQ</b> Micro Gobo Projector	<b>Gantom iQx</b> Controllable Gobo Projector	<b>Gantom One</b> Compact Versatile Pinpoint
PRODUCT HIGHLIGHT	DMX controlled spotlight with high dynamic range dimming, flicker free and video ready.	DMX controlled floodlight with high dynamic range dimming, flicker free and video ready.	World's smallest LED gobo projector. Zoom and focus adjustable. Custom full color images from 35mm slides.	World's smallest LED gobo projector with integrated DMX control. Built-in pattern generator for tunable effects.	Compact 4W pinpoint that exceeds the output of traditional 30W pinpoints. Ultra narrow beam optics and magnetic accessory attachment.
BEAM $\Delta$	19°	28°	25°	25°	2.7° (diffusable with included filters)
FIELD $\Delta$	38°	66°	40°	40°	4.5° (diffusable with included filters)
DIMENSIONS <small>Without Bracket</small>	40mm (1.6") $\varnothing$ x 55.5mm (2.2")	37mm (1.5") $\varnothing$ x 56mm (2.2")	30mm (1.2") $\varnothing$ x 90mm (3.7") Gobo: 19mm (0.75")	30mm (1.2") $\varnothing$ x 90mm (3.7") Gobo: 19mm (0.75")	60mm (2.4") $\varnothing$ x 36.6 (1.4")
ILLUMINANCE <small>1m (3.3ft), 2m (6.6ft), 3m (9.9ft)</small>	883lx (82.0fc), 221lx (20.5fc), 100lx (9.3fc)	407lx (37.8fc), 113lx (10.5fc), 50lx (4.7fc)	510lx (47.4fc), 123lx (11.4fc), 53lx (4.9fc)	510lx (47.4fc), 123lx (11.4fc), 53lx (4.9fc)	22100lx (2053.2fc), 8100lx (752.5fc), 4100lx (380.9fc)
COLOR OPTIONS	 3000K WW 6500K CW DMX Color Control	 3000K WW 6500K CW DMX Color Control	 3000K WW  6500K CW Full Color Gobo	 3000K WW  6500K CW Full Color Gobo	 3000K WW  6500K CW  UV
POWER (12VDC)	4.8W	4.8W	2.8W	2.8W	4.8W
DIMMING	RGBW: 4 Channel DMX Dynamic White: 2 Channel DMX	RGBW: 4 Channel DMX Dynamic White: 2 Channel DMX	PWM	3 Channel DMX: Brightness, Speed, Mode	PWM
SUITABLE ENVIRONMENTS	Indoor or Outdoor (IP65)	Indoor or Outdoor (IP65)	Indoor or Outdoor (IP65)	Indoor or Outdoor (IP65)	Indoor or Outdoor (IP65)
USES	Architainment, theatrical displays, film & television.	Architainment, theatrical displays, film & television.	Retail, architainment, theatrical displays, museum, special effects, and signage.	Retail, architainment, theatrical displays, museum, special effects, and signage.	Centerpiece illumination, event lighting, portable lighting, replacement for traditional pinpoint fixtures.
PRODUCT IMAGE					

[www.gantom.com](http://www.gantom.com)

Address: 28358 Constellation Road Unit 670, Valencia, CA 91355 Phone: 661-347-0779 Fax: 661-793-6985 Email: [info@gantom.com](mailto:info@gantom.com)

